

Control Unit with touch screen 7" - ordered additionally

Original
Quality
Option

Multifunctionality



Multifunctionality

The ergometer can be controlled with a control unit with touch screen. The readout of this control unit is available in more than 15 languages. Various parameters can be visualized: - actual and target angle; - actual and target speed; - distance; - time; - energy; - mode; - height; - heartrate (only available in combination with the HR option); - BPM (only in combination with the BPM option); - SpO2 (only in combination with the SpO2 option).

High standards

Lode is a socially and environmentally responsible company. All Lode products are RoHS/WEE compliant and Lode is ISO 9001:2015, and ISO 13485:2016 certified. All medical products comply to MDD 93/42/EEC, incl. IEC 60601-1.

Reliable and reproducible stress tests

The experience of professionals who calibrate many ergometers showed that the Lode ergometers are the most reliable across the complete workload and rpm range and still within specifications even after many years of intensive use.

Multifunctional usable

The MRI ergometer can be used for cardiac examinations, cardiac research, spectroscopy and other examinations and research.



Original Accessory

Accessory designed and manufactured according to the Lode company quality standards



Compatible with ECG and pulmonary devices

The Lode ergometers have digital interfaces and can be controlled easily by all known stress ECG and pulmonary devices available in the world. This is one of the reasons why the Lode ergometers are very popular worldwide.

**1
watt**

Small adjustment steps

The workload of the Lode ergometers is adjustable in steps of only 1 watt. Depending on your wishes, the test operator or the test subject can adjust the workload. The steps of 1 watt are possible in the manual mode as well as within protocols.



Design

The modern design takes into account the latest requirements in the field of stress testing.



Control Unit with touch screen 7" - ordered additionally

Original
Quality
Option

Multifunctionality

English user interface	✓	Screen resolution	800 x 480 pixels	
Chinese user interface	✓	Product depth (cm)	10 cm	3.9 inch
Croatian user interface	✓	Product length (cm)	24 cm	9.4 inch
Czech user interface	✓	Product width (cm)	18 cm	7.1 inch
Danish user interface	✓			
Dutch user interface	✓			
Finnish user interface	✓			
French user interface	✓			
German user interface	✓			
Greek user interface	✓			
Hungarian user interface	✓			
Italian user interface	✓			
Japanese user interface	✓			
Korean user interface	✓			
Latvian user interface	✓			
Lithuanian user interface	✓			
Norwegian user interface	✓			
Polish user interface	✓			
Portugese user interface	✓			
Romanian user interface	✓			
Russian user interface	✓			
Spanish user interface	✓			
Turkish user interface	✓			
Ukrainian user interface	✓			
Readout actual protocol / step	✓			
Readout Distance	✓			
Readout RPM	✓			
Readout Heartrate	✓			
Readout Energy	✓			
Readout Time	✓			
Readout Mode	✓			
Readout BPM	✓			
Readout SpO2	✓			
Manual operation mode	✓			
Quick start operation mode	✓			
Connectivity				
Lode ERM interface protocol	✓			

Order info

Partnumber: P945834

**Specifications are subject to change without notice.*